


FILL TO REMAIN IN PLACE  
WHEN EARTH MOUND IS REMOVED

GENERAL NOTES : EARTH MOUND TO BE SEEDED WHERE TOTAL DEPTH OF EARTH EXCEEDS 18". ELSEWHERE, EARTH MOUND SHALL BE COVERED WITH WOOD-CHIP MULCH.

THESE DIAGRAMS REPRESENT FILL CONDITIONS ONLY. CUT CONDITIONS SHALL BE SUBJECT TO THE DESIGNER'S DISCRETION TO MEET ACTUAL CONDITIONS. DRAINAGE SHALL BE DESIGNED AS REQUIRED TO MEET FIELD CONDITIONS.

- /1 FLATTER SLOPE IS PREFERRED AND SHALL BE USED WHERE SITE CONDITIONS ALLOW. 6:1 SLOPE IS DESIRABLE.
- /2 APPROACH SHOULDER WIDTH.
- /3 3/8" DENSE GRADED BITUMINOUS CONCRETE.
- /4 WHEN INTERCHANGE IS OPEN TO TRAFFIC. REMOVE 3/8" DENSE GRADED BITUMINOUS CONCRETE, BITUMINOUS CONCRETE LIP CURBING AND EARTH MOUND.



STANDARD SHEET CONN. DEPT. OF TRANSPORTATION	
TYPICAL TEMPORARY EARTH MOUND BARRICADE	
REVISIONS	
NO.	DATE
Δ 4/99	REMOVED DUPLICATE SECTION
Designed by: SPECIAL STUDIES Date: 12-20-88 Drafted by: GLENN L. ARTZ Date: 2-14-89 Reviewed by: M. BURNS Date: 5-1-99 Approval Rec: D. GLADOWSKI Date: 5-1-99 Approved: <i>[Signature]</i> Date: 5-26-99 F.H.W.A. Approval: <i>[Signature]</i> Date: 7-21-99	
Scale: NOT TO SCALE	
STANDARD NUMBER 202	